

suprema

BioStation L2

Fingerprint IP Access Terminal



| BioStation L2 |

Suprema BioStation L2 is an essential fingerprint terminal that provides comprehensive access control and time attendance features based on Suprema's next generation biometric technology and security platform. Designed for all types of time attendance applications, BioStation L2 provides exceptional value by combining World's best Suprema fingerprint algorithm, high performance and enhanced security features.



SUPREMA

BioStation L2

Fingerprint IP Access Terminal



Features



Best-in-class Performance

- Latest Suprema algorithm
- 1.2GHz Quad-Core CPU
- Up to 150,000 matches per second



Improved Accuracy & Security

- New advanced LFD (live finger detection) technique
- Improved OP5 optical sensor and algorithm



Expanded Capacity

- Max. 500k users/1 million text logs
- Large memory: 2GB Flash + 256 MB RAM



Full Time Attendance Features

- 2-inch colour LCD with intuitive GUI
- Full time and attendance functionality
- 3 x 4 numeric touch keypad



Versatile Interfaces/RF options


- Wiegand, RS485, TTL I/O, relay
- 125KHz EM
- 13.56 MHz Mifare/ DESFire/ DESFire EV1/ Felica/NFC

Specifications


Biometric	Fingerprint
Template	SUPREMA/ ISO 19794-2/ ANSI 378
Extractor / Matcher	MINEX certified and compliant
LFD	Supported
RF Option	125 KHz EM 13.56 MHz Mifare/ DESFire/ DESFire EV1/ Felica/NFC
CPU	1.2 GHz Quad-Core
Memory	2GB Flash + 256 MB RAM
Max. User	500,000 (1:1), 100,000(1:N)
Max. Template	1,000,000(1:1), 200,000(1:N)
Max. Logs	1,000,000(text)
LCD	2-inch colour LCD
Sound	16-bit Hi-Fi
Ethernet	10/100 Mbps, auto MDI/MDI-X
RS-485	1ch host or slave (selectable)
Wiegand	1ch input or output (selectable)
TTL	2ch input
Relay	1 Relay
Tamper	Supported
Power	DC 12V
Operating Temperature	-20°C ~ 50°C (-4°F~ 122°F)
Operating Humidity	0% ~ 80%, non-condensing
Dimensions (WxHxD, mm)	71 x 201 x 44 (bottom)/ 34 mm(top) (2.80" x 7.91" x 1.7"(bottom)/ 1.34"(top)
Unit Weight	Device: 280g (0.62lb) Bracket: 61g (0.13lb) including washers/bolts
Certificates	CE, FCC, KC, RoHS, REACH, WEEE

System Configuration


• Standalone



• Standalone-Secure



• Distributed Access Control Systems



neaMetrics (Pty) Ltd

108 11th Street, Parkmore, Johannesburg, 2196

Tel: +27 11 784 3952 | Fax: +27 86 552 0819
enquiry@suprema.co.za | www.suprema.co.za

Approved Suprema Distributor - Africa

